

**Tire dimensions not listed in TDS 2010**

Width	Ratio	Rim	Size	Comment	Decision
135	70	15	540	OK	<b>540</b>
145	65	15	540	OK	<b>540</b>
155	70	14	580	OK	<b>580</b>
165	80	15	620	OK	<b>620</b>
175	50	14	540	OK	<b>540</b>
175	50	15	54	OK	<b>54</b>
175	60	13	54	OK	<b>54</b>
175	80	16	685	OK	<b>685</b>
185	50	14	54	OK	<b>54</b>
185	65	16	620	OK	<b>620</b>
205	40	17	605	OK	<b>605</b>
205	40	18	620	OK	<b>620</b>
205	45	15	580	OK	<b>580</b>
205	70	16	695	OK	<b>695</b>
205	75	14	685	OK	<b>685</b>
205	75	17	697	OK	<b>697</b>
205	75	17.5	697	OK	<b>697</b>
205	80	16	697	OK	<b>697</b>
215	35	19	645	OK	<b>645</b>
215	60	18	695	OK	<b>695</b>
215	65	17	695	OK	<b>695</b>
215	75	16	695	OK	<b>695</b>
215	75	17	697	OK	<b>697</b>
215	80	16	697	OK	<b>697</b>
225	30	19	645	OK	<b>645</b>
225	35	17	605	OK	<b>605</b>
225	40	16	605	OK	<b>605</b>
225	40	17	645	OK	<b>645</b>
225	45	18	695	OK	<b>695</b>
225	45	19	695	OK	<b>695</b>
225	50	19	695	OK	<b>695</b>
225	55	19	697	OK	<b>697</b>
225	60	18	697	OK	<b>697</b>
225	65	17	697	OK	<b>697</b>
225	65	VR390	690	OK	<b>690</b>
225	75	16	697	OK	<b>697</b>
225	80	16	698	OK	<b>698</b>
235	40	19	685	OK	<b>685</b>
235	45	20	697	OK	<b>697</b>
235	50	19	697	OK	<b>697</b>
235	55	19	697	OK	<b>697</b>
235	60	17	695	OK	<b>695</b>
235	60	18	697	OK	<b>697</b>
235	70	17.5	AL59	OK	<b>AL59</b>
235	80	16	698	OK	<b>698</b>
245	35	19	685	OK	<b>685</b>
245	35	20	695	OK	<b>695</b>
245	40	18	685/ 755	OK	<b>685 / 755</b>
245	40	19	695	OK	<b>695</b>
245	45	16	645	OK	<b>645</b>
245	50	17	695	OK	<b>695</b>
245	50	18	695	OK	<b>695</b>
245	55	17	695	OK	<b>695</b>
245	60	16	695	OK	<b>695</b>
245	70	19.5	AL64	OK	<b>AL64</b>
255	30	19	685	OK	<b>685</b>
255	30	20	N.A.!	NA	<b>N.A.</b>
255	35	18	685	OK	<b>685</b>
255	35	19	685	OK	<b>685</b>

255	35	20	N.A.!	NA		<b>N.A.</b>
255	40	17	685	OK		<b>685</b>
255	40	18	N.A.!	NA		<b>N.A.</b>
255	40	19	695	OK		<b>695</b>
255	40	20	697	OK		<b>697</b>
255	45	17	685	OK		<b>685</b>
255	45	18	695	OK		<b>695</b>
255	45	19	697	OK		<b>697</b>
255	45	22	699	OK		<b>699</b>
255	50	18	697	OK		<b>697</b>
255	55	16	695	OK		<b>695</b>
255	55	17	697	OK		<b>697</b>
255	60	18	698	OK		<b>698</b>
255	70	18	699	OK		<b>699</b>
255	75	18	AL64	OK		<b>AL64</b>
265	30	19	N.A.!	NA		<b>N.A.</b>
265	35	18	N.A.!	NA		<b>N.A.</b>
265	40	18	N.A.!	NA		<b>N.A.</b>
265	45	21	698	OK		<b>698</b>
265	70	17.5	AL64	OK		<b>AL64</b>
275	30	19	N.A.!	NA		<b>N.A.</b>
275	30	20	N.A.!	NA		<b>N.A.</b>
275	35	18	N.A.!	NA		<b>N.A.</b>
275	35	19	N.A.!	NA		<b>N.A.</b>
275	35	20	697	OK		<b>697</b>
275	40	18	N.A.!	NA		<b>N.A.</b>
275	40	19	697	OK		<b>697</b>
275	40	20	697	OK		<b>697</b>
275	40	21	698	OK		<b>698</b>
275	45	19	697	OK		<b>697</b>
275	45	20	698	OK		<b>698</b>
275	50	20	699	OK		<b>699</b>
275	55	17	697	OK		<b>697</b>
275	55	20	AL64	OK		<b>AL64</b>
275	70	22.5	AL74	OK		<b>OK</b>
285	30	18	N.A.!	NA		<b>NA</b>
285	30	20	N.A.!	NA		<b>NA</b>
285	40	18	NA	NA		<b>N.A.</b>
285	45	19	N.A.!	NA		<b>NA</b>
285	70	22.5	AL74	OK		<b>AL74</b>
285	75	16	NA	NA		<b>N.A.</b>
295	60	22.5	NA	NA		<b>N.A.</b>
295	30	19	NA	NA		<b>N.A.</b>
295	35	19	NA	NA		<b>N.A.</b>
305	30	19	NA	NA		<b>N.A.</b>
305	70	19.5	AL71	OK		<b>AL71</b>
305	70	22.5	AL79	OK		<b>AL79</b>
315	30	20	NA	NA		<b>N.A.</b>